



Category 7  
Light Appliance  
6 Person Crew Cab

## Category 7 Crew Cab Specifications

CAB CHASSIS:	4x4 Crew Cab
GVM:	6000 kg
DIMENSIONS:	Length 6150 mm, Width 2100 mm, Height 2700 (nominal)
TURNING CIRCLE:	15.8 metres
WHEEL BASE:	3380mm
SEATING:	6 Persons
ENGINE:	4 cylinder OHV diesel 3907cc capacity, Turbo-Intercooled
POWER:	103 kW @ 2900 rpm
TORQUE:	365 Nm @ 1600 rpm
TRANSMISSION:	Gearbox: manual 5 speed direct drive, Constant mesh, synchromesh 2nd-5th. Ratios: 5.380, 3.028, 1.700, 1.000, 0.722 to 1. Reverse 5.380:1. Transfer Case: 2 speed. Ratios: High - 1.090:1, Low - 1.987:1 Full time 4WD, central diff lock. Rear Axle; Ratio 5.714:1 Thorton Locker
AXLE LOADINGS:	(Maximum Operational) Front Axle:- 2600 kg Rear Axle:- 4300 kg
MAIN PUMP:	Single stage centrifugal pump close coupled to a twin cylinder 13.2 kW (19 hp) Semi-Silentpack diesel engine.
PUMP DUTY:	550 litres/min. @ 100 kPa 350 litres/min. @ 700 kPa 100 litres/min. @ 1000 kPa Closed head min: 1100 kPa. Note:- Pump may exceed duty points stated.
PRIMER:	Manually operated diaphragm.
AUX. PUMP:	Single stage pump close coupled to single cylinder petrol engine.
TANK:	1100 litre aluminium painted tank.
FOAM:	Foam induction proportioner with 20 litre foam concentrate storage.
BODY:	Galvanised high tensile steel tray frame with aluminium chequer plate floor. Modular aluminium lockers and side crew protection panels. One 30m live hosereel. Storage for canvas hose, branches, knapsacks, rakehoes, drip torch, extinguisher and standpipe.
CAB SPRAY:	Single point water/foam spray.



Head Office

Locked Mail Bag 17 Granville NSW 2142, Australia

website: [www.rfs.nsw.gov.au](http://www.rfs.nsw.gov.au)

**NSW RURAL FIRE SERVICE**  
*...for our community*